



Horticultural Spraying Solutions

Georgia spray cart

The popular spray cart Georgia is equipped with all modern conveniences. The spray cart Georgia is constructed in such manner that all controls are positioned on one side of the cart as a result of which unnecessary walking around the cart will be avoided. Even the filling hole is positioned, as much as possible, at the side of the tank. The tank can easily be reached for filling purposes, as the wheel boxes buried in the tank makes the whole cart low based. To put it briefly, this extremely user-friendly spray cart which will keep you going for years.



Standard edition:

- Polyethylene liquid tank, 600 or 1000-litre content, highly smooth finishing on the inside as well as on the outside.
- Strainer box in the filling hole.
- Tab cover with ventilation.
- Clean water tank, over 16-litre content with drain tap manufactured in black polyethylene, completely buried in the large tank.
- Because the suction hose is assembled on the bottom, in a deepening, the pump will fully empty the tank as a result of which the residual liquid will be limited to an absolute minimum.
- All horizontal surfaces within the tank are at least 7° slanting.
- A lockable suction filter which enable the filter being cleaned with a full tank.
- A filling pipe with quick connector and a non-return valve are assembled in the tank.
- A water gauge with a scale marking per 50 litres and a drain tap are assembled.
- A pressure relief tap is assembled on the pump.
- There is an injection nozzle in the tank to mix the spray liquids in an optimum manner.
- Four wheel 6 play with brake on the front wheels.
- Various reels, spray guns and options can be assembled.
- Powder coated frame.